



Conti® Thermo-Protect




Insulating molded parts for basic valves

full vulcanized pre-molded parts made of silicone rubber


insulating, weather- / UV Resistant, durable, heat stable, flexible, reusable

Material: silicone rubber
N. diameter: DN20 ... DN100; more on request
Dimension: pre-molded parts, see chart
Density: 480 kg/m³
Thermal conductivity: 0,07 W/mk at 93 °C
Temperature: -50 °C ... 250 °C
Options: custom products, Tubular fabric for pipes, vulcanized and unvulcanized (kneadable) insulation plates




for valves with flanges

N. diameter DN	ø Flange thickness ca. [mm]	Length ca. [mm]	Insulation thickness [mm]	Order code
020	105	206	16	I-CTP-F020
025	115	216	16	I-CTP-F025
025	115	255	16	I-CTP-F025L
032	140	248	16	I-CTP-F032
040	150	268	16	I-CTP-F040
050	165	302	16	I-CTP-F050
065	185	364	16	I-CTP-F065
080	200	394	16	I-CTP-F080
100	220	429	16	I-CTP-F100



for double flanges

N. diameter DN	ø Flange thickness ca. [mm]	Length ca. [mm]	Insulation thickness [mm]	Order code
020	105	62	16	I-CTP-DF020
025	115	62	16	I-CTP-DF025
032	140	71	16	I-CTP-DF032
040	150	80	16	I-CTP-DF040
050	165	76	16	I-CTP-DF050



for ball valves

N. diameter DN	Valve external ca. [mm]	Length ca. [mm]	Insulation thickness [mm]	Order code
015	46 × 46	49	16	I-CTP-STV15*
025	60 × 60	65	16	I-CTP-STV25*
020	55 × 70	56	16	I-CTP-HGH20*
015	46 × 46	49	16	I-CTP-GH15*
025	60 × 60	65	16	I-CTP-GH25*

CTP paste for gluing	Cartouche 300 ml	I-CTP-P300
----------------------	------------------	------------

*STV – with control valve lantern, HGH – with high-cranked lever, GH – with cranked lever